


MB995

ATX Motherboard

8th Gen Intel® Xeon® E / Core™ i7/i5/i3 ATX Motherboard
w/ Intel® C246/ Q370 PCH



Features

- 8th Gen Intel® Xeon® E/ Core™ i7/i5/i3 HC/QC/DC processors, up to 4.7GHz
- 4x DDR4 DIMM, Max. 64GB
- Intel® processor integrated graphics supports DVI-D, HDMI (2.0a) and DisplayPort
- Dual Intel® Gigabit LAN
- 4x USB3.1(10Gbps), 5x USB3.1(5Gbps), 6x COM, 6x SATAIII
- 1x PCI-E(16x), 1x PCI-E(4x), 1x PCI-E(1x), 3x PCI, 1x Mini PCI-E, 2x M.2 (E/ M-key)
- Watchdog timer, Digital I/O, iAMT(11.0), TPM(1.2), vPro, iSMART

Specifications

| | |
|------------------------|--|
| CPU Socket | LGA1151 for 8th Gen Intel® Xeon® E / Core™ i7/i5/i3 HC/QC/DC processors, up to 4.7GHz |
| System Memory | 4x DDR4-2666/ 2400 DIMM, Max. 64GB (supports ECC by CPU SKUs) |
| System Chipset | MB995VF-C246: Intel® C246 PCH MB995VF: Intel® Q370 PCH |
| BIOS | AMI |
| Watchdog Timer | 256 levels |
| SSD | mSATA , NVMe |
| H/W Monitor | Yes |
| Expansion Slot | 1x PCI-E(16x), 1x PCI-E(4x), 1x PCI-E(1x) 3x PCI-E, 1x MiniPCI-E, 1x M.2 (M-key, type:2280) 1x M.2 (E-key, type:2230) |
| VGA Controller | 8th Gen Intel® Core™ i7/i5/i3 processors integrated |
| VGA Memory | Shared memory |
| Display Interface | 1x HDMI (2.0a), 1x DisplayPort (1.2), 1x DVI-D |
| LAN Controller | LAN 1: Intel® I219LM GbE PHY LAN 2: Intel® I210AT GbE (MB995VF-C246), Intel® I211AT GbE (MB995VF) |
| LAN Connector | 2x RJ-45 connectors |
| I/O Chipset | Fintek F81966D-I 4x RS232, 2x RS232/422/485 (jumperless selection) |
| USB | 4x USB3.1 Gen2 (10Gbps) on board 5x USB3.1 Gen1 (5Gbps): -2 ports on board, 2 ports via box-headers -1 port via onboard vertical type connector 2x USB2.0 via pin-header |
| Serial ATA | MB995VF-C246: 6x SATA III MB995VF: 4x SATA III |
| Audio | Intel® C246/Q370 PCH built-in High Definition Audio controller +Realtek audio codec ALC888S-VD2-GR w/ 7.1 channels |
| Others | Digital I/O (4-in/4-out), iAMT (11.6), TPM (2.0), RAID, iSMART (3.5), EUP/ErP |
| Dimensions | 305mm x 244mm (12" x 9.6") |
| Max. Power Requirement | TBD |
| Operating Temperature | 0°C~60°C (32°F~140°F) |
| Storage Temperature | -20°C~80°C (-4°F~176°F) |
| Relative Humidity | 90% (non-condensing @60°C) |

Ordering Information

| | |
|--------------|---|
| MB995VF-C246 | LGA1151 C246 ATX motherboard w/ HDMI, DVI-D, DisplayPort (1.2), dual Gigabit LAN, RAID, iAMT (11.0), TPM (2.0), iSMART (3.5) Art. No. 155287 |
| MB995VF | LGA1151 Q370 ATX motherboard w/ HDMI, DVI-D, DisplayPort (1.2), dual Gigabit LAN, RAID, iAMT (11.6), TPM (2.0), iSMART (3.5) Art. No. 155288 |

Dimensions and Drawing

