

Korenix Industrial Product Selection Guide - SFP / D.D. M. Technology



Fiber Transceiver	Speed	Distance	Wave-length	Operation Temperature	
SFP100MM/SFP100MM-w	Multi-mode	100Mbps	2KM	1310nm	-10~70°C/-40~85°C(W)
SFP100MMD/SFP100MMD-w	Multi-mode	100Mbps DDM	2KM	1310nm	-10~70°C/-40~85°C(W)
SFP100MM5D/SFP100MM5D-w	Multi-mode	100Mbps DDM	5KM	1310nm	-10~70°C/-40~85°C(W)
SFP100SM30/SFP100SM30-w	Single-mode	100Mbps	30KM	1310nm	-10~70°C/-40~85°C(W)
SFP100SM30D/SFP100SM30D-w	Single-mode	100Mbps DDM	30KM	1310nm	-10~70°C/-40~85°C(W)
SFP100SM60/SFP100SM60-w	Single-mode	100Mbps	60KM	1310nm	-10~70°C/-40~85°C(W)
SFP100SM60D/SFP100SM60D-w	Single-mode	100Mbps DDM	60KM	1310nm	-10~70°C/-40~85°C(W)
SFP100SM80/SFP100SM80-w	Single-mode	100Mbps	80KM	1310nm	-10~70°C/-40~85°C(W)
SFP100SM80D/SFP100SM80D-w	Single-mode	100Mbps DDM	80KM	1310nm	-10~70°C/-40~85°C(W)
SFP100SM100/SFP100SM100-w	Single-mode	100Mbps	100KM	1550nm	-10~70°C/-40~85°C(W)
SFP100SM100D/SFP100SM100D-w	Single-mode	100Mbps DDM	100KM	1550nm	-10~70°C/-40~85°C(W)
SFP100SM120/SFP100SM120-w	Single-mode	100Mbps	120KM	1550nm	-10~70°C/-40~85°C(W)
SFP100SM120D/SFP100SM120D-w	Single-mode	100Mbps DDM	120KM	1550nm	-10~70°C/-40~85°C(W)
SFP100SM20B13/SFP100SM20B13-w	Single-mode	100Mbps BIDI/WDM	20km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFP100SM20B13D/SFP100SM20B13D-w	Single-mode	100Mbps BIDI/WDM DDM	20km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFP100SM20B15/SFP100SM20B15-w	Single-mode	100Mbps BIDI/WDM	20km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFP100SM20B15D/SFP100SM20B15D-w	Single-mode	100Mbps BIDI/WDM DDM	20km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFP100SM40B13/SFP100SM40B13-w	Single-mode	100Mbps BIDI/WDM	40km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFP100SM40B13D/SFP100SM40B13D-w	Single-mode	100Mbps BIDI/WDM DDM	40km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFP100SM40B15/SFP100SM40B15-w	Single-mode	100Mbps BIDI/WDM	40km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFP100SM40B15D/SFP100SM40B15D-w	Single-mode	100Mbps BIDI/WDM DDM	40km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFP100SM60B13/SFP100SM60B13-w	Single-mode	100Mbps BIDI/WDM	60km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFP100SM60B13D/SFP100SM60B13D-w	Single-mode	100Mbps BIDI/WDM DDM	60km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFP100SM60B15/SFP100SM60B15-w	Single-mode	100Mbps BIDI/WDM	60km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFP100SM60B15D/SFP100SM60B15D-w	Single-mode	100Mbps BIDI/WDM DDM	60km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFPGSX/SFPGSX-w	Multi-mode	1000Base-SX	550m	850nm	-10~70°C/-40~85°C(W)
SFPGXD/SFPGXD-w	Multi-mode	1000Base-SX DDM	550m	850nm	-10~70°C/-40~85°C(W)
SFPGSX2/SFPGSX2-w	Multi-mode	1000Base-SX	2km	1310nm	-10~70°C/-40~85°C(W)
SFPGX2D/SFPGSX2D-w	Multi-mode	1000Base-SX DDM	2km	1310nm	-10~70°C/-40~85°C(W)
SFPGXLX10/SFPGXLX10-w	Single-mode	1000Base-LX	10km	1310nm	-10~70°C/-40~85°C(W)
SFPGXLX10D/SFPGXLX10D-w	Single-mode	1000Base-LX DDM	10km	1310nm	-10~70°C/-40~85°C(W)
SFPGXLX30/SFPGXLX30-w	Single-mode	1000Base-LHX	30km	1310nm	-10~70°C/-40~85°C(W)
SFPGXLX30D/SFPGXLX30D-w	Single-mode	1000Base-LHX DDM	30km	1310nm	-10~70°C/-40~85°C(W)
SFPGXD50/SFPGXD50-w	Single-mode	1000Base-XD	50km	1550nm	-10~70°C/-40~85°C(W)
SFPGXD50D/SFPGXD50D-w	Single-mode	1000Base-XD DDM	50km	1550nm	-10~70°C/-40~85°C(W)
SFPGZX70/SFPGZX70-w	Single-mode	1000Base-ZX	70km	1550nm	-10~70°C/-40~85°C(W)
SFPGZX70D/SFPGZX70D-w	Single-mode	1000Base-ZX DDM	70km	1550nm	-10~70°C/-40~85°C(W)
SFPGXLX10B13/SFPGXLX10B13-w	Single-mode	1000Base-LX BIDI/WDM	10km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFPGXLX10B13D/SFPGXLX10B13D-w	Single-mode	1000Base-LX BIDI/WDM DDM	10km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)

DDM: Digital Diagnostic Monitoring

Korenix Industrial Product Selection Guide - SFP / D.D. M. Technology



Fiber Transceiver	Speed	Distance	Wave-length	Operation Temperature	
SFPGLX10B15/SFPGLX10B15-w	Single-mode	1000 Base-LX BIDI/WDM	10km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFPGLX10B15D/SFPGLX10B15D-w	Single-mode	1000 Base-LX BIDI/WDM DDM	10km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFPGLX20B13/SFPGLX20B13-w	Single-mode	1000 Base-LX BIDI/WDM	20km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFPGLX20B13D/SFPGLX20B13D-w	Single-mode	1000 Base-LX BIDI/WDM DDM	20km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFPGLX20B15/SFPGLX20B15-w	Single-mode	1000 Base-LX BIDI/WDM	20km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFPGLX20B15D/SFPGLX20B15D-w	Single-mode	1000 Base-LX BIDI/WDM DDM	20km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFPGLX40B13/SFPGLX40B13-w	Single-mode	1000 Base-LX BIDI/WDM	40km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFPGLX40B13D/SFPGLX40B13D-w	Single-mode	1000 Base-LX BIDI/WDM DDM	40km	TX 1310nm, RX 1550nm	-10~70°C/-40~85°C(W)
SFPGLX40B15/SFPGLX40B15-w	Single-mode	1000 Base-LX BIDI/WDM	40km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFPGLX40B15D/SFPGLX40B15D-w	Single-mode	1000 Base-LX BIDI/WDM DDM	40km	TX 1550nm, RX 1310nm	-10~70°C/-40~85°C(W)
SFPGLX60B13	Single-mode	1000 Base-LX BIDI/WDM	60km	TX 1310nm, RX 1550nm	-10~70°C
SFPGLX60B13D	Single-mode	1000 Base-LX BIDI/WDM DDM	60km	TX 1310nm, RX 1550nm	-10~70°C
SFPGLX60B15	Single-mode	1000 Base-LX BIDI/WDM	60km	TX 1550nm, RX 1310nm	-10~70°C
SFPGLX60B15D	Single-mode	1000 Base-LX BIDI/WDM DDM	60km	TX 1550nm, RX 1310nm	-10~70°C

DDM: Digital Diagnostic Monitoring