

Support IEEE 1394a & 1394b

MPX-2213



Features

- Fully Compliant With PCI Express Base Specification, Revision 1.1
- Supports Provisions of IEEE Std P1394b- 2002 and IEEE Std 1394-1995 for IEEE Std 1394a-2000
- Fully Compliant With 1394 Open Host States Controller Interface (OHCI) Specification, Revision 1.1 and Revision 1.2 Draft

Product Description

Host Interface	PCI-E
Controller	XIO2213B
Dimension	30.00mm x 50.95mm
Weight	3g

Operating Conditions

Power Requirement	+3.3V from Mini PCIe +12V from external cable
Temperature	0~70°C
Storage Temperature	-40~+85°C

General Specifications

Compliance	IEEE 1394b (Firewire 400) x1 IEEE 1394b (Firewire 800) x2
Accessories	1 x IEEE1394 IO module 1 x 10PIN cable for single 1394a (OAL1394-DF1410) 1 x 20PIN cable for dual 1394b (OAL1394-DF1420) 1 x DC input cable (OAL4P-6)
Transfer Rate	100M bits/s, 200M bits/s, 400M bits/s, and 800M bits/s (IEEE 1394b).

Ordering Code

MPX-2213 5 ft Bc r% && * * PCI Express mini card supports IEEE1394 Module.

